



Illustrative picture

**SPECIFICS**

<b>Description</b>	Product type	3 ways movable multiplier IP67
	Article code	1452
	Commercial Series	SERIES 13 IEC 309 IP67

<b>General Data</b>	Poles	N° 2P+E	Type of material	Halogen free
	Current	A 16	Type of terminal	Screw PH2
	Voltage	V~ 200-250	Terminal inlet diameter	mm 3,7
	Earth contact position	h 6		
	Degree of protection	IP 67	Dimensional stability	°C -25 /+70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C -25 + 55
	Dimensions LxDxH	cm 225X220X75	Weight	kg 0,5

Behaviour with chemical and atmospheric agents										
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant <span style="color: green;">●</span>	Limited Resistant <span style="color: yellow;">●</span>	Resistant <span style="color: green;">●</span>	Resistant <span style="color: green;">●</span>	Resistant <span style="color: green;">●</span>	Limited Resistant <span style="color: yellow;">●</span>	Limited Resistant <span style="color: yellow;">●</span>	Resistant <span style="color: green;">●</span>	Resistant <span style="color: green;">●</span>	Resistant <span style="color: green;">●</span>	Resistant <span style="color: green;">●</span>

<b>Standards</b>	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

<b>Features package</b>	<b>Descriptions</b>		<b>N/pieces</b>	<b>Weight/kg</b>
	Article		1	0,5
	Package innerbox		3	1,59
	Packaging		./	./

<b>Dimensions</b>		<table border="1"> <thead> <tr> <th rowspan="2">Amp Poles</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>229</td> <td>230</td> <td>266</td> <td>287</td> <td>287</td> <td>287</td> </tr> <tr> <td>B</td> <td>220</td> <td>224</td> <td>256</td> <td>277</td> <td>277</td> <td>281</td> </tr> <tr> <td>C</td> <td>46.5</td> <td>53.5</td> <td>60.5</td> <td>62.5</td> <td>62.5</td> <td>69.5</td> </tr> </tbody> </table>						Amp Poles	16A			32A			3	4	5	3	4	5	A	229	230	266	287	287	287	B	220	224	256	277	277	281	C	46.5	53.5	60.5	62.5	62.5	69.5
		Amp Poles	16A			32A																																			
			3	4	5	3	4	5																																	
		A	229	230	266	287	287	287																																	
B	220	224	256	277	277	281																																			
C	46.5	53.5	60.5	62.5	62.5	69.5																																			



Rev	Date	Technical Manager
01	7/1/20	Romano Pivi

CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT17100000010057