



Illustrative picture

SPECIFICS

<i>Description</i>	Product type	2 ways movable multiplier with plug 16A 50/60 Hz IP44
	Article code	1602
	Commercial Series	SERIES 12 IEC 309 IP44

<i>General Data</i>	Poles	N° 3P+E	Type of material	Abs / Nylon
	Current	A 16	Terminal inlet diameter	mm 3,7
	Voltage	V~ 100-130	Dimensional stability	°C -25 /+70
	Earth contact position	h 4	Resistance glow wire test	°C +650 / +850
	Degree of protection	IP 44	Working temperature	°C , -25 + 55
	Impact Resistance	IK 8	Weight	kg 0,4
	Insulation Resistance	MΩ >10		
	Dimensions LxDxH	cm 22,5x22x7,5		

Behaviour with chemical and atmospheric agents

Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

<i>Standards</i>	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,4
	Package innerbox		4	1,69
	Packaging			

<i>Dimensions</i>		<table border="1"> <thead> <tr> <th>Amp</th> <th colspan="2">16A</th> </tr> <tr> <th>Poles</th> <th>3</th> <th>4</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>164</td> <td>165</td> </tr> <tr> <td>B</td> <td>156</td> <td>160</td> </tr> <tr> <td>C</td> <td>46.5</td> <td>46.5</td> </tr> </tbody> </table>	Amp	16A		Poles	3	4	A	164	165	B	156	160	C	46.5	46.5
	Amp	16A															
Poles	3	4															
A	164	165															
B	156	160															
C	46.5	46.5															



Reg. A.E.E n° IT17100000010057



CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015

Rev	Date	Technical Manager
01	7/1/20	Romano Rosi