



Illustrative picture

SPECIFICS

Description	Product type	Ind.Plug 2P+T 16A - Schuko socket Bip. 10/16A
	Article code	1862
	Commercial Series	SYSTEM ADAPTORS IEC 309 IP20

General Data	Poles	N° 2P+E	Type of material	Halogen free
	Current	A 16	Type of terminal	Screw PH2
	Voltage	V~ 200-250	Terminal inlet diameter	mm 3,7
	Earth contact position	h 6		
	Degree of protection	IP 20	Dimensional stability	°C -25 /+70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C -25 + 55
	Dimensions LxDxH	cm 11,5x5,6x5,6	Weight	kg 0,146

Behaviour with chemical and atmospheric agents											
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays	
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol			
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant	

Standards	CEI EN 50250	/	2014/35/UE
-----------	--------------	---	------------

Features package	Descriptions		N/pieces	Weight/kg
	Article		1	0,146
	Package innerbox		10	1,55
	Packaging		150	23,87

Dimensions			<table border="1"> <tr> <td>Amp</td> <td>16A</td> </tr> <tr> <td>Poles</td> <td>3</td> </tr> <tr> <td>A</td> <td>43,2</td> </tr> <tr> <td>B</td> <td>56</td> </tr> <tr> <td>C</td> <td>46,5</td> </tr> </table>	Amp	16A	Poles	3	A	43,2	B	56	C	46,5
	Amp	16A											
Poles	3												
A	43,2												
B	56												
C	46,5												



Rev	Date	Technical Manager
01	7/1/20	Romano Pivi

CERTIFICATO N° 9105.RO33 - UNI EN ISO 9001:2015

Reg. A.E.E. n° IT17100000010057