














Illustrative picture

SPECIFICS

<i>Description</i>	Product type	Anti-crushing scoket in rubber 16A 250V
	Article code	RS78206
	Commercial Series	ANTI-CRUSHING SERIES

<i>General Data</i>	Poles	N° 2P+E	Type of material	Blend,Nylon
	Current	A 16	Dimensional stability	°C -25 /+70
	Voltage	V~ 250	Resistance glow wire test	°C +650 / +750
	Degree of protection	IP 20	Working temperature	°C , -15 + 35
	Impact Resistance	IK 8	Weight	kg 0,0479
	Insulation Resistance	MΩ >10		
	Dimensions LxDxH	cm 8x5x3		

Behaviour with chemical and atmospheric agents										
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentraded	Diluted	Concentraded	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Limited Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Resistant 

<i>Standards</i>	CEI 23-50	2011/65/UE
------------------	-----------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,0479
	Package innerbox		30	1,527
	Packaging		240	12,836



CERTIFICATO N° 9105.ROSS3 - UNI EN ISO 9001:2015



Reg. A.E.E n° IT17100000010057



Rev	Date	Technical Manager
01	7/1/20	<i>Romano Rossi</i>