












Illustrative picture

SPECIFICS

<i>Description</i>	Product type	6 Schuko Biv.Sockets 10/16A 2P+E 250V, 1,5mt cable H05VV-F 3G1 + LED warning light + lightning arrester + plug 16A 2P+E 250V IT standard P30 P11/17 S17 CEI 23-50
	Article code	RS92125
	Commercial Series	MULTIPLE SOCKETS - SQUARED SERIES

<i>General Data</i>	Poles	N°	2P+E	Type of material	Blend,Nylon					
	Current	A	16	Dimensional stability	°C -25 /+70					
	Voltage	V~	250	Resistance glow wire test	°C +650 / +850					
	Degree of protection	IP	20	Working temperature	°C , -15 + 35					
	Impact Resistance	IK	8	Weight	kg 0,5279					
	Insulation Resistance	MΩ	>10							
	Dimensions LxDxH	cm	26X16X5							
Behaviour with chemical and atmospheric agents										
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Limited Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Resistant 

<i>Standards</i>	CEI 23-50	CEI 23-124	2014/35/UE
------------------	-----------	------------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,5279
	Package innerbox		25	13,2875
	Packaging			



Rev	Date	Technical Manager
01	7/1/20	Romano Pavi