



Illustrative picture

SPECIFICS

<i>Description</i>	Product type	Movable plug low voltage 50/60 Hz IP44
	Article code	9213
	Commercial Series	SERIES 10 IEC 309 IP44

<i>General Data</i>	Poles	N° 2P+E	Type of material	Halogen free
	Current	A 16	Type of terminal	Screw PH2
	Voltage	V~ 200-250	Terminal inlet diameter	mm 3,7
	Earth contact position	h 6	Cable clamp tightening capacity	mm 6,5 - 15
	Degree of protection	IP 44	Dimensional stability	°C -25 /+70
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850
	Insulation Resistance	MΩ >10	Working temperature	°C -,25 + 55
	Dimensions LxDxH	cm 12,5x8,7x8,7	Weight	kg 0,114

Behaviour with chemical and atmospheric agents

Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

<i>Standards</i>	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,114
	Package innerbox		10	1,23
	Packaging		150	19,07

<i>Dimensions</i>		<table border="1"> <thead> <tr> <th rowspan="2">Amp Poles</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>140</td> <td>140</td> <td>140</td> <td>161</td> <td>161</td> <td>161</td> </tr> <tr> <td>B</td> <td>106</td> <td>106</td> <td>106</td> <td>122,5</td> <td>122,5</td> <td>122,5</td> </tr> <tr> <td>C</td> <td>46,5</td> <td>53,5</td> <td>60,5</td> <td>62,5</td> <td>62,5</td> <td>69,5</td> </tr> <tr> <td>D</td> <td>56</td> <td>60,5</td> <td>68</td> <td>72</td> <td>72</td> <td>69</td> </tr> <tr> <td>E</td> <td>6-15</td> <td>6-15</td> <td>8-16</td> <td>11,5-20</td> <td>11,5-20</td> <td>11,5-22</td> </tr> </tbody> </table>						Amp Poles	16A			32A			3	4	5	3	4	5	A	140	140	140	161	161	161	B	106	106	106	122,5	122,5	122,5	C	46,5	53,5	60,5	62,5	62,5	69,5	D	56	60,5	68	72	72	69	E	6-15	6-15	8-16	11,5-20	11,5-20	11,5-22
		Amp Poles	16A			32A																																																	
3	4		5	3	4	5																																																	
A	140	140	140	161	161	161																																																	
B	106	106	106	122,5	122,5	122,5																																																	
C	46,5	53,5	60,5	62,5	62,5	69,5																																																	
D	56	60,5	68	72	72	69																																																	
E	6-15	6-15	8-16	11,5-20	11,5-20	11,5-22																																																	



Rev	Date	Technical Manager
01	7/1/20	Romano Rivi

CERTIFICATO N° 9105.RO53 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT17100000010057