



Illustrative picture

SPECIFICS

Description	Product type	Industrial cable reel HO7RNF 3G2,5 30Mt 3 Ind. 16A 2P+E IP44 Thermal cut-out
	Article code	4001
	Commercial Series	SERIES 4000

General Data	Poles	N° 2P+E	Type of material	Polipropilene/Nylon/pvc/rubber
	Current	A 16	Dimensional stability	°C -25 /+70
	Voltage	V~ 230	Resistance glow wire test	°C +650 / +850
	Earth contact position	h 6	Working temperature	°C , -25 + 55
	Degree of protection	IP 44	Weight	kg 9,4
	Impact Resistance	IK 8		
	Insulation Resistance	MΩ >10		
	Dimensions LxDxH	cm 33x30x40		
	Max power	W 3500		

Behaviour with chemical and atmospheric agents

Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

Standards	CEI EN 61316	2014/35/UE
------------------	--------------	------------

Features package	Descriptions		N/pieces	Weight/kg
	Article		1	9,4
	Package innerbox		1	9,49
	Packaging			

Dimensions	
-------------------	--



CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015



Reg. A.E.E n° IT17100000010057

Rev	Date	Technical Manager
01	7/1/20	Romano Rosi