



Illustrative picture

SPECIFICS

<i>Description</i>	Product type	3 ways movable multiplier with 2 mt flexible cable 50/60 Hz IP67
	Article code	1552
	Commercial Series	SERIES 13 IEC 309 IP67

<i>General Data</i>	Poles	N° 2P+E	Type of material	Halogen free																														
	Current	A 16	Type of terminal	Screw PH2																														
	Voltage	V~ 200-250	Terminal inlet diameter	mm 3,7																														
	Earth contact position	h 6																																
	Degree of protection	IP 67	Dimensional stability	°C -25 /+70																														
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850																														
	Insulation Resistance	MΩ >10	Working temperature	°C , -25 + 55																														
	Dimensions LxDxH	cm 225X220X75	Weight	kg 2,2																														
	Behaviour with chemical and atmospheric agents																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Saline Solution</th> <th colspan="2">Acids</th> <th colspan="2">Bases</th> <th colspan="4">Solvents</th> <th rowspan="2">Mineral Oil</th> <th rowspan="2">UV rays</th> </tr> <tr> <th>Concentrated</th> <th>Diluted</th> <th>Concentrated</th> <th>Diluted</th> <th>Hexane</th> <th>Benzol</th> <th>Acetone</th> <th>Alcohol</th> </tr> </thead> <tbody> <tr> <td>Resistant ●</td> <td>Limited Resistant ●</td> <td>Resistant ●</td> <td>Resistant ●</td> <td>Resistant ●</td> <td>Limited Resistant ●</td> <td>Limited Resistant ●</td> <td>Resistant ●</td> <td>Resistant ●</td> <td>Resistant ●</td> <td>Resistant ●</td> </tr> </tbody> </table>		Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol	Resistant ●	Limited Resistant ●	Resistant ●	Resistant ●	Resistant ●	Limited Resistant ●	Limited Resistant ●	Resistant ●	Resistant ●	Resistant ●	Resistant ●	
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays																								
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol																										
Resistant ●	Limited Resistant ●	Resistant ●	Resistant ●	Resistant ●	Limited Resistant ●	Limited Resistant ●	Resistant ●	Resistant ●	Resistant ●	Resistant ●																								

<i>Standards</i>	CEI EN 60309-1	2014/35/UE
------------------	----------------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	2,2
	Package innerbox		1	2,29
	Packaging		./	./

<i>Dimensions</i>		<table border="1"> <thead> <tr> <th rowspan="2">Amp Poles</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>286</td> <td>285</td> <td>338</td> <td>347</td> <td>347</td> <td>347</td> </tr> <tr> <td>B</td> <td>228</td> <td>234</td> <td>266</td> <td>284</td> <td>284</td> <td>288</td> </tr> </tbody> </table>	Amp Poles	16A			32A			3	4	5	3	4	5	A	286	285	338	347	347	347	B	228	234	266	284	284	288
	Amp Poles	16A			32A																								
3		4	5	3	4	5																							
A	286	285	338	347	347	347																							
B	228	234	266	284	284	288																							



CERTIFICATO N° 9105.ROSS3 - UNI EN ISO 9001:2015



Reg. A.E.E n° IT17100000010057



Rev	Date	Technical Manager
01	7/1/20	Romano Pisci